




PPS工程塑料紧固件 聚苯硫醚(Polyphenylenesulfide)

● 该材料为超级非结晶性工程塑料。具有耐热性，可在高温环境下长期使用不劣化。耐腐蚀性, 机械性能, 尺寸稳定性也非常优越, 被广泛用于电气-电子产品

● 连续使用温度200℃ ● 燃烧性UL94 V-0

	内六角 螺丝 (PPS/CB)		M3	M4	M5	M6	M8	M10	M12
	节距		0.5	0.7	0.8	1	1.25	1.5	1.75
	长度								
	6		○	○					
	8		○	○	○				
	10		○	○	○	○	○		
	12		○	○	○	○	○		
	15		○	○	○	○	○	○	
	20		○	○	○	○	○	○	○
	25				○	○	○	○	○
	30				○	○	○	○	○
	35				○			○	○
40					○	○	○	○	
	六角 螺母 (PPS/NT)	M2.6	M3	M4	M5	M6	M8	M10	M12
	节距	0.45	0.5	0.7	0.8	1	1.25	1.5	1.75
	垫片 (PPS/W)		3	4	5	6	8	10	12
	d x D		3.2x7	4.3x9	5.3x12.5	6.4x12.5	8.4x17	10.5x21	13x24
	厚度t		0.5	0.8	1	1.6	1.6	2	2.5