




U-NUT规格表



1种



2种



3种

螺纹精度: JIS6H (2级)

○ 为标准品
△ 为订制品

螺母本体材质						SS400		S45C	SUS304	订制品	单重[g]			
摩擦片材质						SUS301								
称呼 (d)	节距 (p)	对面宽度 (s)		全厚度 (h)		螺纹高度 (m)	对角高 (e)	2种	1种	2种	1种	3种 (h1)	约 (3种除外)	
		尺寸	公差	尺寸	公差									约
M3	0.5	5.5	0 -0.2	3.2	±0.3	2.7	6.4	△					0.4	
M4	0.7	7		3.8		3	8.1	○			○	3.1	0.8	
M5	0.8	8		4.6		3.9	9.2	○		○	○	4	1.2	
M6	1	10		5.1		4.2	11.5	○		○	○		2.1	
M8	1.25	13	0 -0.25	7.3	±0.4	6.1	15	○		○	○	5	5.1	
	1							△		△				
M10	1.5	17		8.3		7.1	19.6	○		○	○	6.5	10	
	1.25							○		○	△			
M12	1.75	19	0 -0.35	10.5	±0.5	9	21.9	○		○	○	8.5	15.2	
	1.5							△		△	△			
	1.25							○		△	△			
M14	2	22		12.5		11	25.4		○	○	○	9.5	24	
	1.5							○	△	△				
M16	2	24		14.5		13	27.7		○	○	○	12	31.5	
	1.5							○	△	△				
M18	2.5	27		16		14	31.2		○	○	○			45.2
	1.5							△	△	△				
M20	2.5	30		17.5		15.4	34.6		○	○	○	14	61.4	
	1.5							△	△	△				
M22	2.5	32		19.5		17.2	37		○	○	○	74.3		
	1.5		△		△			△						
M24	3	36	21.5	18.8	41.6		○	○	○	16	108			
	2					△	△	△						
M27	3	41	24	21.2	47.3		○	○	○	159				
M30	3.5	46	27	24	53.1		○	○	○	226				
	3					△	△	△						
M33	3.5	50	29.5	26.5	57.7		○	○	△	287				
	3					△	△	△						
M36	4	55	32.5	29.5	63.5		○	○	△	393				
	3					△	△	△						
M39	4	60	35	31.8	69.3		○	○	△	509				
	3					△	△							
M42	4.5	65	38	34.5	75		○	○	△	651				
	3					△	△							
M45	4.5	70	40	36	80.8		○	○	△	794				
	3					△	△							
M48	5	75	42	38	86.5		○	○	△	972				
	3					△	△							
M52	5	80	46	42	92.4		△	△		1190				
M55	3	85	49	44.5	98.1		△	△		1360				
M56	5.5					45	△	△	1410					
	M60	5.5	90	52	47.5	104		△	△	1660				
4		48					△	△						
M64	6	95	54	50	110		△	△	1910					
	4					△	△							